

Product Specification

Product model: **FS25**

Product type: **POD**

Version	V1	Effective Date	10/07/2019
R&D Dept.	0199	Page	4

1. Dimension (Picture and Description)



Description: Pod

Appearance: There is no scratches, cracks, stains, uneven colors, unclear logos, and fades on the appearance of this product.

2. Features

- Transpring® next-gen heating core technology
- Magnetic connection
- Bottom sensor touch
- 3-gear voltage settings

3. Main Technical Parameter

Specifications of Battery	
Battery capacity	140mAh
Resistance	1Ω
Dimension	L18xW10.15xH63.5 (mm)
Weight	10.59g
On/Off mode	Touch 5 times on bottom sensor
Working voltage	3V
Battery life	≥ 300times
Preheating function	Touch 4 times on bottom sensor
Output mode	Constant voltage output
Output voltage	2.6V-3.3V-4.0V
Quiescent current	10-20uA
Vaping mode	Inhale activated
Vaping display	Gear color
Charging display	Battery color
Charging mode	Micro USB port
Charging voltage	4.2V~5.5V
Charging current	140mA
Appearance material	Plastic + aluminum alloy
Storage Temperature	23°C±5°C
Working Temperature	-10°C~+50°C

Specifications of Cartridge	
Tank Volume	0.5ml
Resistance	1.2Ω
Aperture Size	Φ0.9/Φ1.2/Φ1.6mm
Aperture Number	4
Dimension	L18xW10.15xH26.35 (mm)
Weight	4.64g
Heating Core Material	Nichrome
Oil Drawing Material	Ceramic
Tank Material	PCTG
Appearance material	Plastic + aluminum alloy
Storage Temperature	23°C±5°C
Working Temperature	-10°C~+50°C

4. How to Use

1. Fill the tank with your favorite oil.
2. Insert the stopper into tank with a special jig within 2 minutes.

Notes:

- Do not inject the oil into the airway!*
- Do not top off the tank with oil.*



5. Notes

1. Please keep out of reach of children;
2. Use a qualified adapter to charge the product;
3. In order to ensure the normality of the battery when the product is not used for a long time, please charge the product once every month.

6. Storage

1. The storage temperature is 23±5°C and the humidity is 50±10% RH.

2. Place in a cool, dark and ventilated place.